

## SAFETY SURVEY

Area of Hazard \_\_\_\_\_

Hazard \_\_\_\_\_

Speakman Part # \_\_\_\_\_

Area of Hazard \_\_\_\_\_

Hazard \_\_\_\_\_

Speakman Part # \_\_\_\_\_

Area of Hazard \_\_\_\_\_

Hazard \_\_\_\_\_

Speakman Part # \_\_\_\_\_

Client Facility \_\_\_\_\_

Address \_\_\_\_\_

City \_\_\_\_\_

State \_\_\_\_\_ Zip \_\_\_\_\_

Telephone \_\_\_\_\_

Contact Person \_\_\_\_\_

Distributor \_\_\_\_\_

Distributor's Representative \_\_\_\_\_

Telephone \_\_\_\_\_

Date \_\_\_\_\_

## EMERGENCY EQUIPMENT PERFORMANCE SPECIFICATIONS

### EYE & EYE FACE WASHES

Eyewashes - .4 GPM

Eye/Face Washes - 3 GPM

Nozzles protected from airborne contaminants  
Provide flushing fluid to both eyes simultaneously at a  
velocity low enough to be non-injurious.

Simple operation – “off” to “on” in 1 second or less

Height from standing surface 33” to 45”

Nozzles located 6” from nearest wall or obstruction

Minimum operating pressure – 30 psi

Hands free operation

### SHOWERS

Minimum flow of 20 GPM

Simple operation – “off” to “on” in 1 second or less

Height from standing surface 82” – 96”

Pattern: 20” diameter @ 60” above standing surface

Center of spray located 16” from any obstruction

Minimum supply pipe size – 1”

Hands Free Operation

All Emergency equipment needs to be connected to a supply  
that will allow for a minimum of 15 minutes of operation

All Emergency equipment is required to be third party  
certified for compliance to the ANSI Standard

# SPEAKMAN®

P.O. Box 191, Wilmington, DE 19899

Phone 800-537-2107

Fax 800-977-2747

www.speakmancompany.com

## SPEAKMAN COMPANY

### ANSI Z358.1

### EMERGENCY EQUIPMENT SURVEY

*Do your employees work with any of  
the following hazardous materials:*

AUTOMOTIVE FLUIDS  
CLEANSING AGENTS  
PAINTS AND SOLVENTS  
ACIDS AND BASES  
CORROSIVE CHEMICALS  
BATTERY ACIDS  
LABORATORY CHEMICALS

ANY AREA WHERE SPLASH, HAND & EYE  
PROTECTION IS REQUIRED

*If in doubt, check the MSDS sheet!*

ACCORDING TO OSHA 29 CFR 1910.151,  
Subpart k, sec.c

*“Where the eyes or body of any person may  
be exposed to injurious corrosive materials,  
suitable facilities for quick, drenching or  
flushing of the eyes and body shall be  
provided within the work area for immediate  
emergency use.”*

<i>Do you have proper coverage?</i>	<i>ANSI Z358.1 Recommends</i>	<i>Speakman Solutions</i>
<b>1</b> <i>Are there hazards present that can injure the eyes or body?</i>	Provide recommended Emergency Equipment within 10 seconds travel time of the hazard (ANSI Z358.1)	Eyewashes (Series, SE-500) Eye/Face Washes (Series SE-400) Drench Showers (Series SE-200) Combination Eyewashes & Showers (Series SE-600)
<b>2</b> <i>Does the unit work when activated?</i>	Equipment shall be in good working order and meet ANSI performance specifications	If no, refer to manufacturers instructions or select appropriate Speakman product
<b>3</b> <i>Is the equipment located in unheated areas where freezing conditions exist?</i>	Equipment shall be protected from freezing or freeze protected equipment shall be installed	Series SE-6000 heat traced equipment Frost Proof Units SE-4500 heated GravityFlo®
<b>4</b> <i>Is the hazard in an area where there is no potable water available?</i>	Equipment shall be accessible and within 10 seconds travel time	Portable units (Series SE-4700, SE-4000 & SE-590)
<b>5</b> <i>Is the flushing fluid too cold or too hot for use?</i>	Delivered flushing fluid shall be tepid. (Check with medical advisor for optimum temperature)	Speakman Thermostatic Mixing Valves (Series, SE-350, SE-360 & SE-370)
<b>6</b> <i>Is personal eyewash equipment such as hand held drench hoses or squeeze bottles the only means of flushing the eyes or body?</i>	<b>Personal eyewash equipment does not meet the criteria of plumbed or self-contained eyewash equipment</b> Personal eyewash equipment supports plumbed and self-contained units but shall not replace them	Choose Speakman showers or eyewashes to meet areas requirements
<b>7</b> <i>Is the Emergency equipment tested on a regular basis?</i>	Equipment shall be tested weekly to verify proper operation and inspected annually to assure conformance with ANSI Z358.1 requirements	Speakman Test Tags (P/N 91-0635 ) and Shower Tester (P/N SE-950)
<b>8</b> <i>Is the Emergency Equipment accessible?</i>	Emergency Equipment shall be located on the same level as the hazard and the path shall be free of obstructions	Make sure paths to Emergency Equipment are clear and free of obstructions
<b>9</b> <i>Is the Emergency equipment properly identified?</i>	Equipment shall be identified w/ highly visible signs	Safety Equipment Signs (SGN1, SGN2, SGN3)
<b>10</b> <i>Is there proper lighting near the Emergency equipment?</i>	The area shall be well lighted & highly visible	Speakman VPL option or provide lighting
<b>11</b> <i>Are your employees familiar with the operation of the Emergency equipment?</i>	Employees who may be exposed to hazardous materials shall be instructed in the location and proper use of emergency equipment	Speakman Installation, Operation and Maintenance Sheets are available through “Quick Facts” Fax Back service. Call (888)822-5606

This information should only be used as a guide to identify the basic requirements for Emergency Equipment as recommended by ANSI Z358.1. To ensure that you are in compliance with OSHA 29 CFR 1910.151 Subpart k, sec. “c” and ANSI Z358.1 please refer to the current standard or consult with an OSHA representative.