SPEAKMAN®

P.O. Box 191, Wilmington, DE 19899-0191 USA
1-800-537-2107 Fax: 1-800-977-2747
www.speakmancompany.com

ANYSTREAM 2000®

Showerheads

S-2005

GENERAL SPECIFICATION

Polished chrome plated Anystream 2000 showerhead. Swivel ball connector. Spray adjusting T-handle. 3-1/4" face. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray channels for a full body coverage pattern. Center core nozzle delivers eight pulsating massage jets. Combination spray available. Product is equipped with an integral EZ Connection sealing device for ease of assembly to the shower arm. Requires no tools or Teflon tape in most installations. Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum to meet existing ANSI A112.18.1M standard.

❑ S-2005

Anystream 2000 polished chrome showerhead with integral volume and velocity control ring allows a full range of flow options for individual intensity preferences as well as water and energy conservation.

❑ S-2005-HOTEL

Anystream 2000 polished chrome showerhead.

S-2005-HOTEL

OPTIONS

SUFFIX	DESCRIPTION
❑ BB	Bright brass finish
❑ BP	Blister pack packaging
❑ WHT	White finish

This space for Architect/Engineer approval.

Anystream 2000 — Registered T.M. Speakman Company
© Copyright, Speakman Company, 2006